

STRONGHOLD® | BUTYL



SIMPLIFIED FLASHLESS SOLUTION

- One-step Butyl application
- Minimize labor with one step installation using the pre-applied, peel and install, butyl design
- Reliable waterproofing without messy sealant
- Eliminate risk of roof damage. No more disturbing shingles

OPTIMIZED FOR NXT UMOUNT, UNIRAC'S OPEN CHANNEL RAIL SYSTEM

- Open slot design for ease of rail connectivity with included STRONGHOLD™ NXT UMOUNT® rail clamp
- STRONGHOLD™ Butyl combined with the NXT UMOUNT® system make installation and wire management a breeze
- UL Certified with NXT UMOUNT®

DUAL MOUNTING OPTIONS

- Pre-attached butyl pad: Simply peel, stick, and fasten with the two (2) included screws for rafter mount
- For direct-to-deck applications, simply install additional decking screws

ADDITIONAL BENEFITS

- Competitively priced with standard rafter attachments

WHY STRONGHOLD™ BUTYL?

Unirac's STRONGHOLD™ Butyl is efficient, dependable, and optimized for UNIRAC's NXT UMOUNT® system. The pre-applied butyl pad removes the need for additional flashing. Just peel the liner, place the attachment, and fasten it to the roof. In addition, the butyl, used throughout the roofing and solar industries for its reliability, conforms to the screws and roof for a robust, dependable seal with no extra work! Couple this with the NXT UMOUNT® system, and you have a highly reliable, easy-to-install system with integrated wire management

KITTED WITH

- ONE (1) Stronghold™ Butyl direct-to-deck attachment with pre-applied butyl patch. (Extra patches for shimming available.)
- TWO (2) screws for rafter installation (Additional screws for direct-to-deck applications available.)
- ONE (1) NXT Rail Clamp

